This listing of claims will replace all prior versions, and listings, of claims in the

application.

Please cancel claims 1-19.

20. (New): A mobile lawn and garden sprayer, comprising:

a chassis mounted on a plurality of wheels and having a push handle (a)

attached to the chassis for allowing a user to manually push the sprayer

through thick turf:

(b) a container carried by the chassis for containing a liquid for being sprayed;

a battery carried on the chassis for supplying power to a pump connected to (c)

the container for discharging the liquid from the container under pressure;

a spray head positioned on a front end of the chassis and operably

connected to the pump, the spray head being oriented to producing an

evenly-dispersed forward projecting discharge of the liquid under pressure;

and

(d)

a spray wand carried by the lawn and garden sprayer and removable (e)

therefrom, the spray wand being operably connected to the pump for

discharging the liquid under pressure at a location remote from the chassis.

3

Appl. No. 10/695,162 Amdt. dated 11/6/2006 Reply to Office Action of 5/4/2006
21. (New): The mobile lawn and garden sprayer according to claim 20, wherein the
plurality of wheels includes a pair of spaced-apart rear wheels and a pair of spaced-apart
front wheels.
22. (New): The mobile lawn and garden sprayer according to claim 21, wherein the rear
wheels have a larger diameter than the front wheels for allowing easy movement of the
sprayer through thick turf.
23. (New): The mobile lawn and garden sprayer according to claim 20, wherein the pump

is connected to the container by at least one flexible hose.

Reply to Office Action of 5/4/2006

 $24.\,$ (New): The mobile lawn and garden sprayer according to claim 20, wherein the spray

head comprises at least one nozzle mounted to the chassis for producing an evenly-

dispersed forward projecting discharge of the liquid under pressure.

25. (New): The mobile lawn and garden sprayer according to claim 20, and further

including a tee connected to a discharge port of the pump for allowing connection of the

spray wand and the spray head to the pump.

26. (New): The mobile lawn and garden sprayer according to claim 25, wherein the spray

wand and the spray head are each connected to the tee by a flexible hose for producing

a forward projecting discharge of the liquid.

Reply to Office Action of 5/4/2006

 $\,$ 27. (New): The mobile lawn and garden sprayer according to claim 20, wherein the spray

head comprises two nozzles mounted to the chassis for producing an evenly-dispersed

forward projecting discharge of the liquid under pressure.

28. (New): The mobile lawn and garden sprayer according to claim 27, and further

including a splitter for dividing liquid flow from the pump into a first flow and a second flow,

the first flow being directed to a first one of the two valves and the second flow being

directed to a second one of the two valves.

29. (New): The mobile lawn and garden sprayer according to claim 28, wherein the splitter

includes a first valve for shutting off the first flow and a second valve for shutting off the

second flow.

6

Reply to Office Action of 5/4/2006

30. (New): A mobile lawn and garden sprayer, comprising:

(a) a chassis having an interior cavity mounted on a plurality of wheels and

having a push handle attached to the chassis for allowing a user to manually

push the sprayer through thick turf;

(b) a container carried within the interior cavity for containing a liquid for being

sprayed;

(c) a battery carried within the interior cavity for supplying power to a pump

connected to the container for discharging the liquid from the container under

pressure;

(d) a spray head positioned on a front end of the chassis and operably

connected to the pump, the spray head being oriented to produce a forward

projecting discharge of the liquid under pressure; and

(e) a spray wand carried by the lawn and garden sprayer and removable

therefrom, the spray wand being operably connected to the pump for

discharging the liquid under pressure at a location remote from the chassis.

7

Reply to Office Action of 5/4/2006

31. (New): The mobile lawn and garden sprayer according to claim 30, wherein the

interior cavity is defined by sides that form a continuous rim on a top edge of the chassis,

wherein the top edge defines a female strengthening ring for adding strength to the

chassis.

32. (New): The mobile lawn and garden sprayer according to claim 31, wherein the

container has a male strengthening ring for adding strength and mating with the female

strengthening ring of the chassis.

33. (New): The mobile lawn and garden sprayer according to claim 30, wherein the

plurality of wheels includes a pair of spaced-apart rear wheels and a pair of spaced-apart

front wheels.

Reply to Office Action of 5/4/2006

34. (New): The mobile lawn and garden sprayer according to claim 33, wherein the rear wheels have a larger diameter than the front wheels for allowing easy movement of the sprayer through thick turf.

35. (New): The mobile lawn and garden sprayer according to claim 30, wherein the pump is connected to the container by at least one flexible hose.

36. (New): The mobile lawn and garden sprayer according to claim 30, wherein the spray head comprises at least one nozzle mounted to the chassis for producing an evenly-dispersed forward projecting discharge of a liquid under pressure.

Reply to Office Action of 5/4/2006

37. (New): The mobile lawn and garden sprayer according to claim 30, wherein the spray head and spray wand are each operably connected to the pump by a flexible hose for

producing a forward projecting discharge of the liquid under pressure.

38. (New): The lawn and garden sprayer according to claim 30, and further including a

back cover adjacent to the container and attached to the chassis for covering the power

supply and the pump within the interior cavity of the chassis.

39. (New): The lawn and garden sprayer according to claim 19, wherein the back cover

has a male strengthening ring for mating with the female strengthening ring of the chassis.